

# High Performance Plugs

## OPV

PRONAL OPV are able to handle **3 bars of back pressure** and allow operations on different types of pipes (concrete, HDPE, steel, PVC, etc.). A large range is available, with the stopper allowing for **sealing until 2500 mm**. Larger diameter, back-pressure resistance or particular specification stoppers can also be developed by our engineering team.



## OHP

OHP are dedicated to contain high **back pressure of up to 25 bars and more**. They allow the same operations as OPV but can be used in pipes where back pressure is more important.

Such stoppers can also be used in numerous fields to bring buoyance, weld inspection control, valve repair, or valve replacement.



PLUG

OPV OHP	STOPPER DIAMETER (mm)	MIN SEALING Ø (mm)	MAX SEALING Ø (mm)	LENGTH (mm)	MAX BACK PRESSURE (bar)		
					OPV	OHP 1	OHP 2
90	90	95	145	230	3	8	15
140	140	145	190	280	3	8	15
185	185	190	245	370	3	8	15
240	240	245	290	550	3	8	15
280	280	290	385	560	3	8	15
380	380	385	490	685	3	8	15
480	480	490	595	970	3	8	15
530	530	535	700	1345	3	8	15
690	690	700	900	1140	3	8	15
840	840	850	1000	1395	3	8	15
990	990	1000	1300	1640	3	8	15
1090	1090	1100	1400	1890	3	8	15
1290	1290	1300	1550	2220	3	8	15
1490	1490	1550	1895	2770	3	8	15
1890	1890	1895	2200	3210	3	8	15