



## Direct solenoid and solenoid pilot operated valves



Function	Port size	Flow (Max)	Circuit bar mounting	Series
<b>3/2 NO-NC</b>	<b>1/4" –3/8"</b>	<b>Cv 2.0</b>	<b>Non plug-in</b>	<b>53</b>

### OPERATIONAL BENEFITS

1. The 4-way pilot develops maximum shifting force both ways
2. Memory spring available
3. Balanced spool, immune to variations of pressure, also provides high flow
4. Short stroke with high flow
5. Bonded spool with minimum friction, shifting in a glass-like finished bore
6. Pilot with balanced poppet, high flow, short and consistent response times.
7. Wiping effect eliminates sticking
8. Long service life



### HOW TO ORDER

Pilot air	NC Valve	NO Valve
		
Internal	53A-1A0- <b>xx-xxxx-xxx</b>	53A-2A0- <b>xx-xxxx-xxx</b>
External from 10 end	53A-1B0- <b>xx-xxxx-xxx</b>	53A-2B0- <b>xx-xxxx-xxx</b>

### SOLENOID OPERATOR

DM – D **xx x** – **x xx**

XX	Voltage	X	Wire length	X	Manual Operator	XX	Electrical connection
JA	110/50, 120/60	A	18"	1	Non locking	BA	Flying leads
JB	220/50, 240/60	B	24"	2	Locking	KA	Mini square connector
JC	24/60	J <sup>†</sup>	6"			KD	Mini square connector with light
FB	24VDC (1,8W)					JB	Rectangular connector
DA	24VDC (5,4W)					JD	Rectangular connector with light
DF	24VDC (12,7W)						

<sup>†</sup> For use with "J" and "K" type connectors

GM – G **xx x** – **x xx**

XX	Voltage	X	Wire length	X	Manual Operator	XX	Electrical connection
DC	24VDC (1,8W)	A	18"	1	Non locking	BA	Flying leads
DD	24VDC (2,5W)	B	24"	2	Locking	BT	Flying leads with light
DF	24VDC (4,0W)	C	36"			KA	Solenoid plug-in wire assembly
						KT	Solenoid plug-in wire assembly with light
						GA	MAC JAC solenoid plug-in wire assembly

### HOW TO ORDER CIRCUIT BAR

Port size	Pilot air	Side cylinder ports	Bottom cylinder ports
1/4" NPTF	Internal	EBM053A-00AAA- <b>xx</b>	EBM053A-00BAA- <b>xx</b>
	External	EBM053A-00ABA- <b>xx</b>	EBM053A-00BBA- <b>xx</b>
3/8" NPTF	Internal	EBM053A-00AAB- <b>xx</b>	EBM053A-00BAB- <b>xx</b>
	External	EBM053A-00ABB- <b>xx</b>	EBM053A-00BBB- <b>xx</b>

**xx** = Number of stations



www.LDA.be - LDA@LDA.be - + 32(0)2-266 13 13

## Direct solenoid and solenoid pilot operated valves

### TECHNICAL DATA

<b>Fluid:</b>	Compressed air, vacuum, inert gases
<b>Pressure range:</b>	Internal pilot: 20 to 120 PSI External pilot: Vacuum to 120 PSI
<b>Lubrication:</b>	Not required, if used select a medium aniline point lubricant (between 180°F and 210°F)
<b>Filtration:</b>	40μ
<b>Temperature range:</b>	0°F to 120°F (-18°C to +50°C)
<b>Orifice:</b>	8,5 mm
<b>Flow:</b>	1/4": Cv 1.7 – 3/8": Cv 2.0
<b>Coil:</b>	Epoxy encapsulated - Class A wires – 100% ED (specify mod. 0449)
<b>Voltage range:</b>	-15% to +10% of nominal voltage
<b>Protection:</b>	IP54 (GM pilot) – IP64 (DM pilot)
<b>Power:</b>	1,0 to 5,4W (Higher wattages available)

Options: BSPP threads

### DIMENSIONS

Shown with BA connector

